

HP Z600 WORKSTATION

Maximum computing power in minimal space

The HP Z600 packs eight-core compute and visualization power into a small, quiet package—for the ideal workstation when every inch, watt, and decibel make a difference.

Innovation that transforms the way you work

The HP Z600's sleek new industrial design—brushed aluminum, tool-less access chassis, integrated handles, and visually cable-less engineering—creates new standards for ease of service, lowered acoustics, and energy efficiency.

- Enhance your work area with HP's quietest workstation, designed to fit where space is at a premium
- Minimize power and cooling costs with ENERGY STAR® qualified configurations featuring 85% efficient power supplies and an HP-developed energy-saving feature that helps lower energy consumption in off mode
- See, share, and show your work across the world with the new HP SkyRoom⁹collaboration solution, which combines real-time 3D graphics sharing and video conferencing

Performance to help you accomplish more every minute

The HP Z600 is engineered to optimize the way processor, memory, graphics, OS and software technology work together to deliver massive, whole-system computational power.

- Tackle bigger problems faster and process more tasks and threads in parallel with the new Intel® QuickPath Technology and new Intel® Xeon® processors¹ with integrated memory controllers.
- Get maximum I/O bandwidth and expandability from a range of Gen2 PCI Express slots and optical drives and up to 5 storage bays
- Choose the simplified HP Installer Kit for Linux installation or a breadth of Microsoft® Windows® selections
- Drive up to 8 displays with new dual graphics support and the latest NVIDIA and ATI graphics cards

Reliable and legendary confidence-inspiring quality

- Close relationships with ISVs help ensure full certification for your applications
- In-depth testing and quality assurance keep you productively up-and-running
- HP Performance Tuning Framework helps ease configuration and updates and maximize a range of applications
- Comprehensive, lifetime HP Total Care options provide personal attention, convenient tools, and reliable service

HP Z600 WORKSTATION

HP recommends Windows Vista® Business

Genuine Windows Visto® Business 32-bit with downgrade to Windows® XP Professional 32-bit custom installed* Genuine Windows Visto® Business 42-bit ** Genuine Windows Visto® Business 42-bit ** Genuine Windows Visto® Business 42-bit ** HP Installer Kir for Linux (includes drivers for both 32-bit and 64-bit CS versions of Red Hat Enterprise Linux WS4 and WS5) Inte® Xeono processor* ES550*, 20.06 Ftg. 4 MB cache, 800 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 4 MB cache, 800 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 8 MB cache, 1036 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 8 MB cache, 1006 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 8 MB cache, 1006 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 8 MB cache, 1006 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES550*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor* ES500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor*, 25500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor*, 25500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor*, 25500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor*, 25500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor*, 25500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core Intel Xeon processor*, 25500*, 20.06 Ftg. 8 MB cache, 1033 MHz memory, Quad-Core	Form factor	Rackable minitower
Intel Xeon processor ¹² E5506 ³ , 2.2 GBt. 8, MB cache, 1066 MHz memory, Quad-Core Intel Xeon processor ¹² E5520 ³ , 2.2 GBt. 8, MB cache, 1066 MHz memory, Quad-Core Intel Xeon processor ¹² E5520 ³ , 2.2 GBt. 8, MB cache, 1066 MHz memory, Quad-Core Intel Xeon processor ¹² E5540 ³ , 2.33 GHz, 8 MB cache, 1036 MHz memory, Quad-Core Intel Xeon processor ¹² E5550 ³ , 2.6 GBt. 8, MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5500 ³ , 2.6 GBt. 8, MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570 ³ , 2.93 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ¹² E5570	Operating systems	Genuine Windows Vista® Business 32-bit with downgrade to Windows® XP Professional 32-bit custom installed* Genuine Windows Vista® Business 64-bit with downgrade to Windows® XP Professional x64 custom installed* Genuine Windows Vista® Business 32-bit** Genuine Windows Vista® Business 64-bit**
Memory 6 DIMM slots, up to 24 GB (expected availability May 2009), 6-channel DDR3 1333 MHz**, 3 channels per CPU (**actual memory speed dependent on processor capability) Integrated SATA 3 GB/s controller, RAID 0, 1, 5, 10 capable; Optional SAS controller, LSI 3041E 4-port SAS/SATA, RAID 0, 1, 10 capable Up to (3) 3.5-inch 7200 rpm SATA drives: 160, 250, 320, 500 GB, 1, 1.5* TB, 4.5 TB max*; Up to (4) 2.5-inch 10K rpm SATA drives; 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drive expected availability 9/09). Note: Third and fourth drives occupy one external optical bay. Optical drives Optical drives DVD-ROM, DVD+/-RW, Slot-load DVD+/-RW, Blu-Ray Writer (expected availability May, 2009) 2 external 5.25-inch bays, 2 internal 3.5-inch HDD bays, Up to 4 eSATA. Note: Third and fourth HDDs occupy one external bay. Slots 2 PCI Express Gen2 x 16, 1 PCI Express Gen2 x 8 mechanical/x4 electrical, 1 PCI Express Gen1 x 8 mechanical/x4 electrical, 2 PCI Professional 2D: NVIDIA Quadro NVS 295 (256 MB), NVIDIA Quadro NVS 450 (512 MB) Midrange 3D: NVIDIA Quadro RY 380 (256 MB), ATI FirePro V3700 (256 MB), NVIDIA Quadro FX 580 (512 MB) Midrange 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V3700 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB),	Available processors	Intel Xeon processor ^{1,2} E5506 ³ , 2.13 GHz, 4 MB cache, 800 MHz memory, Quad-Core Intel Xeon processor ^{1,2} E5520 ³ , 2.26 GHz, 8 MB cache, 1066 MHz memory, Quad-Core Intel Xeon processor ^{1,2} E5530 ³ , 2.40 GHz, 8 MB cache, 1066 MHz memory, Quad-Core Intel Xeon processor ^{1,2} E5540 ³ , 2.53 GHz, 8 MB cache, 1066 MHz memory, Quad-Core Intel Xeon processor ^{1,2} E5550 ³ , 2.66 GHz, 8 MB cache, 1333 MHz memory, Quad-Core Intel Xeon processor ^{1,2} E5560 ³ , 2.80 GHz, 8 MB cache, 1333 MHz memory, Quad-Core
memory speed dependent on processor capability) Drive controllers ⁵ Integrated SATA 3 GB/s controller, RAID 0, 1, 5, 10 capable; Optional SAS controller, LSI 3041E 4-port SAS/SATA, RAID 0, 1, 10 capable Hard drive(s) ⁶ Up to (3) 3.5-inch 7200 rpm SATA drives: 160, 250, 320, 500 GB, 1, 1.5* TB, 4.5 TB max; Up to (4) 2.5-inch 10K rpm SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB, 1.35 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB, 1.35 TB max; Up to (4) 2.5-inch 10K rpm SATA drives: 160, 300 GB, 1.35 TB max; Up to (4) 2.5-inch 10K rpm SATA drives: 160, 300 GB, 1.35 TB max; Up to (3) 3.5-inch 15K rpm SATA drives: 160, 300 GB, 1.35 TB SATA drives: 160, 300 GB, 1	Chipset	Intel® 5550
1, 10 capable Up to (3) 3.5-inch 7200 rpm SATA drives: 160, 250, 320, 500 GB, 1, 1.5* TB, 4.5 TB max*; Up to (4) 2.5-inch 10K rpm SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drives expected availability 9/09). Note: Third and fourth drives occupy one external optical bay. DVD-ROM, DVD+Y/RW, Slot-load DVD+Y/RW, Blu-Ray Writer (expected availability May, 2009) 2 external 5.25-inch bays, 2 internal 3.5-inch HDD bays, Up to 4 eSATA. Note: Third and fourth HDDs occupy one external bay. Slots 2 PCI Express Gen2 x16, 1 PCI Express Gen2 x8 mechanical/x4 electrical, 2 PCI Professional 2D: NVIDIA Quadro NVS 295 (256 MB), NVIDIA Quadro NVS 450 (512 MB) Entry 3D: NVIDIA Quadro NVS 295 (256 MB), NVIDIA Quadro NVS 450 (512 MB) Midranga 3D: NVIDIA Quadro FX 380 (256 MB), ATI FirePro V3700 (325 MB), NVIDIA Quadro FX 580 (512 MB) Midranga 3D: NVIDIA Quadro FX 3800 (768 MB), ATI FirePro V3700 (512 MB) High-end 3D: NVIDIA Quadro FX 3800 (768 MB), ATI FirePro V7700 (61 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro CX Audio Network Network Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 leEE 1394a (optional), 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical	Memory ⁴	
SÀTA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5 TB SATA drive expected availability 9/09). Note: Third and fourth drives occupy one external optical bay. DVDROM, DVD+/-RW, Slot-load DVD+/-RW, Blu-Ray Writer (expected availability May, 2009) 2 external 5.25-inch bays, 2 internal 3.5-inch HDD bays, Up to 4 eSATA. Note: Third and fourth HDDs occupy one external bay. 2 PCI Express Gen2 x16, 1 PCI Express Gen2 x8 mechanical/x4 electrical, 1 PCI Express Gen1 x8 mechanical/x4 electrical, 2 PCI Professional 2D: NVIDIA Quadro NVS 295 (256 MB), NVIDIA Quadro NVS 450 (512 MB) Entry 3D: NVIDIA Quadro FX 380 (256 MB), ATI FirePro V3700 (256 MB), NVIDIA Quadro FX 580 (512 MB) Midrange 3D: NVIDIA Quadro FX 1800 (768 MB), ATI FirePro V5700 (512 MB) High-end 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro CX Audio High Definition Integrated RealTek ALC262 Audio, optional Creative X-Fi Titanium PCle Audio Card, optional HP Thin USB Powered Speakers Network Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) 17.5 x 6.5 x 17.3 in (44.51 x 16.53 x 44 cm) Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies HP LP1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP3065 30-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD	Drive controllers ⁵	
Optical drives 7 Drive bays 2 external 5.25-inch bays, 2 internal 3.5-inch HDD bays, Up to 4 eSATA. Note: Third and fourth HDDs occupy one external bay. 2 external 5.25-inch bays, 2 internal 3.5-inch HDD bays, Up to 4 eSATA. Note: Third and fourth HDDs occupy one external bay. 2 PCI Express Gen2 x16, 1 PCI Express Gen2 x8 mechanical/x4 electrical, 1 PCI Express Gen1 x8 mechanical/x4 electrical, 2 PCI Professional 2D: NVIDIA Quadro NVS 295 (256 MB), NVIDIA Quadro NVS 450 (512 MB) (Intry 3D: NVIDIA Quadro FX 380 (256 MB), ATI FirePro V3700 (256 MB), NVIDIA Quadro FX 580 (512 MB) (Intry 3D: NVIDIA Quadro FX 3800 (768 MB), ATI FirePro V3700 (256 MB), NVIDIA Quadro FX 580 (512 MB) (Intry 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1 GB), ATI FirePro V7750 (1 GB), ATI FirePro V7750 (1 GB), ATI FirePro V7750 (1 GB), ATI FirePr	Hard drive(s) ⁶	SATA drives: 160, 300 GB SFF, 1.2 TB max; Up to (3) 3.5-inch 15K rpm SAS drives: 146, 300, 450 GB, 1.35 TB max (*1.5
Slots 2 PCI Express Gen2 x16, 1 PCI Express Gen2 x8 mechanical/x4 electrical, 1 PCI Express Gen1 x8 mechanical/x4 electrical, 2 PCI Professional 2D: NVIDIA Quadro NVS 295 (256 MB), NVIDIA Quadro NVS 450 (512 MB) Entry 3D: NVIDIA Quadro FX 380 (256 MB), ATI FirePro V3700 (256 MB), NVIDIA Quadro FX 580 (512 MB) Midrange 3D: NVIDIA Quadro FX 3800 (768 MB), ATI FirePro V5700 (512 MB) High-end 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro CX Audio High Definition Integrated RealTek ALC262 Audio, optional Creative X-Fi Titanium PCIe Audio Card, optional HP Thin USB Powered Speakers Network Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) Power supply Monitors (screen size diagonally measured) Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Optical drives ⁷	DVD-ROM, DVD+/-RW, Slot-load DVD+/-RW, Blu-Ray Writer (expected availability May, 2009)
electrical, 2 PCI Graphics (dual graphics on selected cards) Professional 2D: NVIDIA Quadro NVS 295 (256 MB), NVIDIA Quadro NVS 450 (512 MB) Entry 3D: NVIDIA Quadro FX 380 (256 MB), ATI FirePro V3700 (256 MB), NVIDIA Quadro FX 580 (512 MB) Midrange 3D: NVIDIA Quadro FX 1800 (768 MB), ATI FirePro V5700 (512 MB) High-end 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro CX Audio High Definition Integrated RealTek ALC262 Audio, optional Creative X-Fi Titanium PCIe Audio Card, optional HP Thin USB Powered Speakers Network Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies HP LP1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP2475w 24-inch Widescreen ICD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen ICD Monitor	Drive bays	2 external 5.25-inch bays, 2 internal 3.5-inch HDD bays, Up to 4 eSATA. Note: Third and fourth HDDs occupy one external bay.
(dual graphics on selected cards) Midrange 3D: NVIDIA Quadro FX 380 (256 MB), ATI FirePro V3700 (256 MB), NVIDIA Quadro FX 580 (512 MB) Midrange 3D: NVIDIA Quadro FX 1800 (768 MB), ATI FirePro V5700 (512 MB) Midrange 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro CX Migh Definition Integrated RealTek ALC262 Audio, optional Creative X-Fi Titanium PCle Audio Card, optional HP Thin USB Powered Speakers Network Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) 17.5 x 6.5 x 17.3 in (44.51 x 16.53 x 44 cm) Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies Monitors (screen size diagonally measured) Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor Mon	Slots	
Midrange 3D: High-end 3D: NVIDIA Quadro FX 1800 (768 MB), ATI FirePro V5700 (512 MB) High-end 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA Quadro CX High Definition Integrated RealTek ALC262 Audio, optional Creative X-Fi Titanium PCle Audio Card, optional HP Thin USB Powered Speakers Network Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) Power supply Monitors (screen size diagonally measured) Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Graphics	
Audio High Definition Integrated RealTek ALC262 Audio, optional Creative X-Fi Titanium PCle Audio Card, optional HP Thin USB Powered Speakers Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies HP LP1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP2475w 24-inch Widescreen LCD Monitor Monitor Monitor Monitor Monitor Monitor Monitor Monitor	cards)	Midrange 3D: NVIDIA Quadro FX 1800 (768 MB), ATI FirePro V5700 (512 MB) High-end 3D: NVIDIA Quadro FX 3800 (1 GB), ATI FirePro V7750 (1 GB), NVIDIA Quadro FX 4800 (1.5 GB), NVIDIA
Ports Front: 3 USB 2.0, 1 IEEE 1394a (optional), 1 microphone in, 1 headphone out Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies HP LP 1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP2475w 24-inch Widescreen LCD Monitor Monitor HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Audio	High Definition Integrated RealTek ALC262 Audio, optional Creative X-Fi Titanium PCle Audio Card, optional HP Thin USB
Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional) Internal: 3 USB 2.0 Input devices PS/2 standard keyboard, USB standard keyboard, USB Smart Card Keyboard, USB 2-button optical scroll mouse, USB 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse Dimensions (H x W x D) Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies HP LP 1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP2475w 24-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Network	Integrated Broadcom 5764 LAN, TPM 1.2 Controller, Optional Broadcom NIC, Optional Intel NIC
3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse 17.5 x 6.5 x 17.3 in (44.51 x 16.53 x 44 cm) Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies Monitors (screen size diagonally measured) HP LP1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP2475w 24-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Ports	Rear: 6 USB 2.0, 1 audio in, 1 audio out, 1 microphone in, 2 PS/2, 1 RJ-45 to integrated Gigabit LAN, 1 serial (optional)
Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies Monitors (screen size diagonally measured) HP LP 1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP2475w 24-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Input devices	3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Scroll Mouse
Power supply 650-Watt 85% efficient power supply; direct connection Power Supplies Monitors (screen size diagonally measured) 650-Watt 85% efficient power supply; direct connection Power Supplies HP LP1965 19-inch LCD Monitor, HP LP2275w 22-inch Widescreen LCD Monitor, HP LP2475w 24-inch Widescreen LCD Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Dimensions (H x W x D)	17.5 x 6.5 x 17.3 in (44.51 x 16.53 x 44 cm)
diagonally measured) Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD Monitor	Power supply	
	Monitors (screen size diagonally measured)	Monitor, HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HP LP3065 30-inch Widescreen LCD
	Warranty	

*Windows Vista Business disk may also be included for future upgrade if desired. To qualify for this downgrade an end user must be a business (including governmental or educational institutions) and is expected to order at least 25 customer systems with the same custom image.

**Certain Windows Vista product features require advanced or additional hardware. See www.microsoft.com/windowsvista/getready/hardwareregs.mspx and

www.microsoft.com/windowsvista/getready/capable.mspx for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit www.windowsvista.com/upgradeadvisor.

Quad-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits; check with software provider to determine suitability; Not all customers or software applications will necessarily benefit from use of these technologies.

² 64-bit computing on Intel architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See www.intel.com/info/em64t for

³ Intel's numbering is not a measurement of higher performance.

⁴ Each processor supports up to 3 channels of DDR3 memory. To realize full performance at least 1 DIMM must be inserted into each channel. To get full 6 channel support, 2 processors MUST be installed. 5 SATA hardware RAID is not supported on Linux systems. The Linux kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. Please visit http://h20000.www2.hp.com/bc/docs/support/SupportManual/c00060684/c00060684.pdf for RAID capabilities with Linux.

6 For hard drives, 1 GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 12 GB of hard drive (or system disk) is reserved for the system recovery software (XP and XP Pro). Up to 3 GB of system disk is reserved for system recovery software. (Vista).

7 Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players. ⁸ HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at www.hp.com/go/lookuptool. Additional HP Care Pack Services information by product is available at www.hp.com/hps/carepack. Service levels and response times for HP Care Packs may vary depending on your geographic location. 9 SkyRoom will be available August 2009



© 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Xeon, and QuickPath are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. Windows Vista is either a registered trademark ortrademark of Microsoft Corporation in the United States and/or other countries.

4AA2-4397ENW, February 2009